

# Product Sheet MASKING TAPE MTE-YELLOW







### MASKING TAPE MTE-YELLOW

High bake refinishing? This is it

## Superior waterproof and UV resistance

Advanced paper and resin technologies combine to produce a material suitable for indoor and outdoor applications



110° C temperature resistance



Extremely flexible and conformable



Natural rubber resin



# Product Sheet MASKING TAPE MTE-YELLOW

#### Features and Benefits

Excellent adhesion	<b>&gt;&gt;</b>	Good mechanical strength
Flexible	<b>&gt;&gt;</b>	Easy to shape on contours
Solvent resistant	<b>&gt;&gt;</b>	Paint will not bleed
Consistency of thickness	<b>&gt;&gt;</b>	Uniform paint edge
Easy roll release	<b>&gt;&gt;</b>	Easy to apply
Waterproof backing	<b>&gt;&gt;</b>	Indoor & outdoor use
110 °C temp rating	<b>&gt;&gt;</b>	High bake refinishing
UV resistant	<b>&gt;&gt;</b>	Easy clean removal without adhesive transfer

#### **Substrates**

Old paint Fillers Primers Top Coats Clear Coats Fibre Glass Gel Coat Glass Soft and Resinous Wood Wood Coatings Wooden Floors Walls and Dry Walls Painted Surface Primed Surface Composite Plastic

### **Applications**

Paint and Decorative masking	
Construction masking	
Industrial masking	
Aerospace masking	
Automotive masking	
Marine masking	



# Product Sheet MASKING TAPE MTE-YELLOW

#### Suited for





Automotive Refinishing

Composite Industries

### **Technical Specifications**

Colour	Yellow	Yellow	Yellow	Yellow
Width	18 mm	24 mm	36 mm	48 mm
Length	50 m	50 m	50 m	50 m
Adhesive	Natural rubber	Natural rubber	Natural rubber	Natural rubber
Thickness	0,145 mm	0,145 mm	0,145 mm	0,145 mm
Temperature R	esistance 110° - 60 min	110° - 60 min	110° - 60 min	110° - 60 min
RemovalTime	Indoor 10 days	10 days	10 days	10 days
RemovalTime	Outdoor 7 days	7 days	7 days	7 days
Elongation at B	reak 9%	9%	9%	9%
Adhesion to Ste	eel 300 g/cm	300 g/cm	300 g/cm	300 g/cm
RollingBallTes	t 1 cm	1 cm	1 cm	1 cm
Tensile Strengt	h 5,0 kg/cm	5,0 kg/cm	5,0 kg/cm	5,0 kg/cm
Waterproof	Yes	Yes	Yes	Yes